



JEM Compact Hazer Pro

Robust yet small and lightweight, the JEM COMPACT HAZER PRO is a versatile haze machine designed for the highly demanding professional market. Its ability to produce exceptional atmospheric haze effects in a short period of time while operating at low noise levels make it ideal for nearly any application from shows and events to theatre, TV studios, clubs, cruise ships, theme parks and more.

FEATURES

TECHNICAL SPECIFICATIONS

GALLERY



Physical

Length: 532 mm (21.0 in.)

Width: 224 mm (8.9 in.)

Height: 278 mm (11.0 in.)

Height with hanging bracket: 296 mm (11.7 in.)

Weight, dry: 8.5 kg (18.8 lbs.)

Weight, filled: 11 kg (24.3 lb.)

Performance

Coverage volume: 3800 m³ (134,196 ft³) per minute

Operating time with 2.5 l fluid (min/max): 20/70 Hours

Continuous effect output

Ready time: 1 minute

Control and Programming

Control options: Digital control panel, DMX, optional digital remote control, master/slave link mode

Control parameters: Continuous or timer-controlled output

Haze and fan: Independent variable output, 0-100%

DMX channels: 3 (Haze, Fan, Control)

Self-cleaning cycle: Manually engaged or DMX

DMX compliance: ANSI E1.11 - USITT DMX512-A

Construction

Housing: Steel & aluminum

Color: Black

Heat exchanger: 900 W, Thermally protected

Blower fan: Integrated, 200-2500 RPM

Airflow control: Optional Air Director

Fluid pump: Oscillating piston, high pressure

Fluid management: Fluid out sensing, sealed for transportation

Fluid reservoir: 2.5 l drop-in reservoir with quick-connect fitting

Installation

Mounting: Standing or optional hanging kit

Orientation: Up to +/- 30° from horizontal

Clearance around machine: 100 mm (4 in.)

Connections

AC Power: Neutrik PowerCon

DMX, link mode in/out: 5-pin locking XLR

Remote control: 3-pin locking XLR

Firmware: AVR socket

Electrical

EU model

AC power : 220-240 V, 50/60 Hz

Main fuse: 6.3 AT (slow blow) 250 V

Typical power and current: 1010 W, 4.4 A*

US model

AC power: 110-120 V, 50/60 Hz

Main fuse: 10 AT (slow blow) 125 V

Typical power and current: 1042 W, 8.68 A*

*Measurements made at nominal voltage. Allow for a deviation of +/- 10% :

Thermal

Maximum ambient temperature (Ta max.): 40° C (104° F)

Minimum ambient temperature (Ta min): 5° C (41° F)

Exterior surface temperature, steady state: 30° C (86° F)

Maximum nozzle temperature: 290° C (554° F)

Approvals

EU model
EU safety: EN 60335-1+A15, EN 62233
EU EMC: EN 61000-6-3
EU Immunity: EN 61000-6-1
Australia/NZ (pending): RCM

US model
US safety: UL 998 (pending)
Canada safety: CSA C22.2 No 104-01 (pending)
Calibration factors have been developed and approved by the Actors' Equity Association and the Broadway League for use in measuring theatrical haze with the JEM Compact Hazer Pro™ and JEM C-Plus Haze Fluid™
Included Items
Fluid reservoir, 2.5 l: P/N 34300521
Power input cable, EU, powerCON, stripped ends, 2.5 m (8.2 ft): P/N 11501041
Power input cable, US, powerCON, molded NEMA 5-15P, 2.5 m (8.2 ft): P/N 11501042

Accessories
JEM Compact Hazer Pro™ Air Director: P/N 92625011
JEM Compact Hazer Pro™ Digital Remote Control: P/N 92765040
JEM Compact Hazer Pro™ Flying Kit: P/N 92610003

Approved fluids
JEM™ C-Plus Haze Fluid
JEM™ Pro Clean Supreme
**Various sizes available - contact your dealer or see 'Fluids' product pages for details*

Installation Accessories
G-clamp: P/N 91602003
Half-coupler clamp: P/N 91602005
Quick trigger clamp: P/N 91602007
Safety cable, SWL 60 kg, BGV C1/ DGUV 17, black: P/N 91604006

Service Tools
Epsilon 5 AVR Programmer: P/N 50502004
Temperature Calibration Box: P/N 92620005

Ordering Information
JEM Compact Hazer Pro™, EU: P/N 92225950
JEM Compact Hazer Pro™, US: P/N 92225960

